

Polygon Shading :-


Process of applying illumination model to surface points.

approaches :-

- ① Flat Shading
- ② Gouraud Shading
- ③ Phong Shading


Flat Shading :-

One intensity for the whole polygon
constant shading for each face.



Select a point P on the face
Find normal to the face n_p .
Find intensity I at P
Fill the polygon with I .

- Computationally Fast
- Not smooth
- Match Band effects



Polygon mesh approximation



Rendered with flat shading

Flat shading provides an accurate rendering if

- ① The object does not have a curved surface.
- ② All light sources illuminating the object are

sufficiently far from the surface.

- ③ The viewing position is sufficiently far from the surface.

Gouraud Shading:- (Henri Gouraud, 1971)

Smooth Shading



Rendered with flat shading



Rendered with Gouraud Shading

INTERPOLATION:- Intensity values for each polygon are matched with the values of adjacent polygon.

STEPS:-

- ① Determine the average unit normal vector at each polygon vertex.
- ② Apply an illumination model to each vertex to calculate the vertex intensity.
- ③ Linearly interpolate the vertex intensities over the surface of the polygon.




FIGURE 35
The normal vector at vertex V is calculated as the average of the surface normals for each polygon sharing that vertex.

Unit Normal at a vertex V is average of normals of the polygons incident at the vertex.

$$N_v = \frac{\sum_{k=1}^n N_k}{|\sum_{k=1}^n N_k|}$$




FIGURE 36
For Gouraud surface rendering, the intensity at point 4 is linearly interpolated from the intensities at vertices 1 and 2. The intensity at point 5 is linearly interpolated from intensities at vertices 2 and 3. An interior point p is then assigned an intensity value that is linearly interpolated from intensities at positions 4 and 5.

⇒ We now we have vertex normals N_1, N_2, N_3 .
Compute the intensities at these vertices using these normals and some illumination model.

⇒ I_1, I_2, I_3





FIGURE 36
For Gouraud surface rendering, the intensity at point 4 is linearly interpolated from the intensities at vertices 1 and 2. The intensity at point 5 is linearly interpolated from intensities at vertices 2 and 3. An interior point p is then assigned an intensity value that is linearly interpolated from intensities at positions 4 and 5.




⇒ Fill the polygon using scan line conversion and interpolation.

$$I_4 = \frac{y_4 - y_2}{y_1 - y_2} I_1 + \frac{y_1 - y_4}{y_1 - y_2} I_2 \quad \text{--- (1)}$$

$$I_5 = \frac{y_5 - y_3}{y_2 - y_3} I_2 + \frac{y_2 - y_5}{y_2 - y_3} I_3 \quad \text{--- (2)}$$



using (1) and (2)



$$I_p = \frac{x_5 - x_p}{x_5 - x_4} I_4 + \frac{x_p - x_4}{x_5 - x_4} I_5$$

Calculation of intensities along incremental scan lines,

FIGURE 37
Incremental interpolation of intensity
values along a polygon edge for
successive scan lines.



using equation ①/②

$$I = \frac{y-y_2}{y_1-y_2} I_1 + \frac{y_1-y}{y_1-y_2} I_2 \quad \text{--- ③}$$

To obtain intensity I' for the next line

$$y = y-1 \quad \text{in eq ②}$$

$$\begin{aligned} I' &= \frac{(y-1)-y_2}{y_1-y_2} I_1 + \frac{y_1-(y-1)}{y_1-y_2} I_2 \\ &= \frac{(y-y_2-1)I_1}{y_1-y_2} + \frac{(y_1-y+1)I_2}{y_1-y_2} \\ &= \frac{(y-y_2)I_1 - I_1}{y_1-y_2} + \frac{(y_1-y)I_2 + I_2}{y_1-y_2} \\ &= \frac{(y-y_2)I_1}{y_1-y_2} + \frac{(y_1-y)I_2}{y_1-y_2} + \frac{I_2 - I_1}{y_1-y_2} \\ &= I + \frac{I_2 - I_1}{y_1 - y_2} \end{aligned}$$

$$I' = I + \frac{I_2 - I_1}{y_1 - y_2}$$

⇒ Successive intensity values down the edges is computed simply by adding constant term $\frac{I_2 - I_1}{y_1 - y_2}$ to the previous intensity value.



Drawbacks of Gouraud Shading :-

- ⇒ Highlights on the surface are sometimes displayed with some shapes and linear intensity interpolation causes bright/dark intensity streaks, called **Match Bands**.
- ⇒ Can be reduced by dividing the surface into ↑ polygons
- ⇒ more precise intensity calculations.

Phong Shading :- "Phong Bui Tuong" 1973

Interpolation of normal vectors instead of the intensity values.

Then compute intensity at each point.




FIGURE 38
Interpolation of surface normals along a polygon edge.

STEPS :-

- ① Determine the average unit normal vector at each vertex of the polygon.

- ② Interpolate the vertex normals linearly over the projected area of the polygon.
- ③ Apply an illumination model at positions along scan lines to calculate pixel intensities using the interpolated normal vectors.

Normal vector N is interpolated vertically from the normal vectors at vertices ① and ②

$$N = \frac{y - y_2}{y_1 - y_2} N_1 + \frac{y_1 - y}{y_1 - y_2} N_2$$

⇒ Apply incremental methods for obtaining normal vectors on successive scan lines and at successive pixel positions along scan lines.